

ALLIANCE

OUTDOOR LIGHTING

2017



INTELLIGENT TRANSFORMERS.....4-5
 LED LAMPS6-7
 AREA LIGHTS.....8-11
 PATH LIGHTS.....12
 BULLET LIGHTS.....14-15
 DOWN LIGHTS.....16-17
 FLOOD LIGHTS.....18
 IN-GROUND LIGHTS.....20-22
 STEP LIGHTS.....24-29
 UNDERWATER LIGHT.....30
 WALL SCONCE LIGHTS.....31
 POST LIGHT.....32
 DEMOKIT.....33
 TRANSFORMERS.....34-35
 ACCESSORIES.....36-37
 DOUBLE WIRE LEAD.....38
 ORDER FORM39



available in:

scan for app



App Store



Google play



it150
150 Watt Intelligent Transformer
Two Commons, Two 14V Taps

it300
300 Watt Intelligent Transformer
Three Commons, Three 14V Taps



Features:

- Bluetooth Enabled*
- Astronomical Timer*
- Phone App Driven*
- Multiple 14.0 Volt Taps*
- Lifetime Warranty*
- For LED Only*




BL300-LED8W

- Tower lamps feature:
- Operating voltage: 8v -24v
 - IP Grade: IP67
 - CRI of Ra>80
 - 50,000 hour average life span
 - Ambient operating temperature from -32°F to 162°F, -36°C to 72°C

- PAR36 Lamps feature:
- Warm white color, 2800K temperature
 - Operating voltage: 8v -24v
 - CRI of Ra>80
 - 50,000 hour average life span
 - Ambient operating temperature from -32°F to 162°F, -36°C to 72°C
 - EMI filter
 - IP Grade: IP66

LBIPIN-LED-200lm

2.5 watt bipin, 200 lumens
IP67 certified



LBIPIN-LED-250lm

3 watt bipin, 250 lumens
IP67 certified

L3156-LED-200lm

2.5 watt 3156 wedge base, 200 lumens
IP67 certified



L3156-LED-250lm

3 watt 3156 wedge base, 250 lumens
IP67 certified

LBA15S-LED-200lm

2.5 watt single bayonet, 200 lumens
IP67 certified



LBA15D-LED-200lm

2.5 watt double bayonet, 200 lumens
IP67 certified



L921T5-LED-200lm

2.5 watt T5 wedge base, 200 lumens
IP67 certified



IP67 Certified

IP67: Lamps are dust tight and can be submerged in up to one meter of water



LPAR36-LED-4W-F

4 watt PAR36, 250 lumens, 20 degree

LPAR36-LED-4W-WF

4 watt PAR36, 250 lumens, 40 degree
(20 watt PAR36 equivalent)



LPAR36-LED-8W-F

8 watt PAR36, 300 lumens, 20 degree

LPAR36-LED-8W-WF

8 watt PAR36, 300 lumens, 40 degree
(35 watt PAR36 equivalent)



LPAR36-LED-10W-F

10 watt PAR36, 400 lumens, 30 degree

LPAR36-LED-10W-WF

10 watt PAR36, 400 lumens, 45 degree
(50 watt PAR36 equivalent)



IP66 Certified

IP66: Lamps are dust tight and can withstand powerful water jets from any direction.



LMR16-LED-4W-F

4 watt MR16, 250 lumens
Flood, 45 degree
(20 watt MR16 equivalent)

Available Options:



LMR16-LED-4W-2700K

2700K Color Temperature



LMR16-LED-4W-WF

Wide Flood, 60 degree



LMR16-LED-4W-NS

Narrow Spot, 15 degree



LMR16-LED-6W-F

6 watt MR16, 400 lumens
Flood, 45 degree
(50 watt MR16 equivalent)

Available Options:



LMR16-LED-6W-2700K

2700K Color Temperature



LMR16-LED-5W-F

5 watt MR16, 310 lumens
Flood, 45 degree
(35 watt MR16 equivalent)

Available color options:

LMR16-LED-5W-RED

LMR16-LED-5W-BLUE

LMR16-LED-5W-GREEN

LMR16-LED-5W-AMBER

LMR16-LED-5W-PURPLE

Available Options:



LMR16-LED-5W-2700K

2700K Color Temperature



LMR16-LED-5W-WF

Wide Flood, 60 degree



LMR16-LED-5W-NS

Narrow Spot, 15 degree



LMR16-LED-310lm

Enclosed Housing
Recommended for Down Light Series



LMR11-LED-4W-F

4 watt MR11, 175 lumens
Flood, 45 degree
(20 watt MR11 equivalent)

- MR16 and MR11 LED lamps feature:
- Warm white color, 2900K temperature
 - Operating voltage between 8v-24v
 - CRI of Ra>80
 - 50,000 hour life span
 - Ambient operating temperature from -32°F to 162°F, -36°C to 72°C
 - EMI Filter



BL200-LED6W



Area Light Hats Feature:
 *Note: Area light stems are sold separately

- Brass area light hat, aged brass finish
- Polycarbonate frosted lens
- Polycarbonate clear lens (except for AL700, AL750, AL800 and AL850)
- Rubber gaskets
- Adjustable brass collar with thumb screw (AL700, AL750, AL800 and AL850)
- Lifetime warranty

Area Light Stems Sold Separately:

- ALSTEM12 – 12" Stem
- ALSTEM18 – 18" Stem
- ALSTEM24 – 24" Stem
- ALSTEM60 – 60" Stem
- ALSTEMADJ – 18"-29" Stem

Photo Courtesy of: Michael Epaul Photography
 Lighting Design by: Illumascape Lighting, LLC owned by Phil Costello



10 ALLIANCE



TIKI Features:

*Note: Area light stems are sold separately

- Brass area light hat, aged brass finish
- Metal snuffing cap with chain
- Wick with brass holder
- Solid brass collar
- Lifetime warranty

TIKI

ALSTEM60-LED5W-AMBER

TIKI
Specialty Area Light Hat



PERMAPOST
Heavy Duty Ground Stake



ALSTEM60-LED
with PERMAPOST included
(LBIPIN-LED-200lm lamp included)



ALSTEM24-LED
(LBIPIN-LED-200lm lamp included)



ALSTEM18-LED
(LBIPIN-LED-200lm lamp included)



ALSTEM12-LED
(LBIPIN-LED-200lm lamp included)




AL100

ALSTEMADJ-LED
(LBIPIN-LED-200lm lamp included)



AREA LIGHT STEMS 11



AL400

ALSTEM12-LED

Area Light Stems Feature:

*Note: Area light hats are sold separately

- Brass stem, aged brass finish
- Adjustable brass collar with thumb screw (ALSTEM60 excluded)
- Ceramic bi-pin socket
- Double wire lead pre-connected to the fixture, 16 awg (UL listed), brown
 - 25 foot wire lead, pre-stripped for easy wire connection
 - 18 inch wire lead, LED connection ready
- Plastic ground stake (8.5 in; 21.6 cm length) (ALSTEM60 excluded)
- PermaPost ABS stake with brass cap on ALSTEM60
- Lifetime warranty on fixture housing
- Available without a lamp

12 PATH LIGHTS

PL100-LED
(LBIPIN-LED-200lm lamp included)



PL200-LED
(LBIPIN-LED-200lm lamp included)



PL250-LED
(LBIPIN-LED-200lm lamp included)



PL100-LED Features:

- Brass fixture, aged brass finish
- Solid brass hat with dual adjustments, brass thumb screw for vertical adjustments, brass stem nut for horizontal adjustments
- Ceramic bi-pin socket
- Frosted bubble lens
- Double wire lead pre-connected to the fixture, 16 awg (UL listed), brown
 - 25 foot wire lead, pre-stripped for easy wire connection
 - 18 inch wire lead, LED connection ready
- Plastic ground stake
- Lifetime warranty on fixture housing
- Available without a lamp

PL200-LED and PL250-LED Feature:

- Solid brass area light hat
- Clear glass lens
- Adjustable brass stem, 17"-27" length, aged brass finish
- Ceramic bi-pin socket
- 25 Foot wire lead, 16 awg (UL listed), brown, pre-connected to the fixture, pre-stripped for easy wire connection
- Solid brass stake (8.5 in; 21.6 cm length)
- Lifetime warranty on fixture housing
- Available without a lamp



ALLIANCE 13




Photo Courtesy of: Joe Traina
Lighting Design by: Ryan Hughes Design

14 ALLIANCE

Bullet Lights Feature:

- Brass fixture, aged brass finish
- Cast brass knuckle with dial adjustment
- Fully adjustable brass shroud (CGBL01 comes with turn and lock fitting)
- Ceramic bi-pin socket with lamp clip (MR11 and MR16)
- Clear glass lens (BL300 excluded)
- Double wire lead pre-connected to the fixture, 16 awg (UL listed), brown
 - 25 foot wire lead, pre-stripped for easy wire connection
 - 18 inch wire lead, LED connection ready
- Plastic ground stake (8.5 in; 21.6 cm length) (CGBL01 comes with commercial grade brass stake collar)
- Lifetime warranty on fixture housing
- Available without a lamp



BL300-LED8W

BL300-LED8W

BL200-LED5W

BL200-LED5W

BL200-LED5W

BULLET LIGHTS 15



BL50-LED
(4 watt MR11 LED lamp included)



BL100-LED6W
(6 watt MR16 LED lamp included)

BL100-LED5W
(5 watt MR16 LED lamp included)

BL100-LED4W
(4 watt MR16 LED lamp included)



BL200-LED6W
(6 watt MR16 LED Lamp included)

BL200-LED5W
(5 watt MR16 LED Lamp included)

BL200-LED4W
(4 watt MR16 LED Lamp included)



BL300-LED10W
(10 watt PAR36 LED Lamp included)

BL300-LED8W
(8 watt PAR36 LED Lamp included)

BL300-LED4W
(4 watt PAR36 LED Lamp included)

**Available in LED ONLY*



Available in MR16 Version
PART #: BL350-LED



CGBL01-LED6W
(6 watt MR16 LED lamp included)

CGBL01-LED5W
(5 watt MR16 LED lamp included)

CGBL01-LED4W
(4 watt MR16 LED lamp included)



Hanging Lights Feature:

- Brass fixture, aged brass finish
- Cast brass base with ring
- Adjustable brass shroud on HL100
- Brass shroud with twinkle cutouts on HL200
- Ceramic bi-pin socket with lamp clip on HL100
- Ceramic bi-pin socket on HL200
- Threaded aged brass chain, 18" length
- 25 Foot wire lead, 16 awg (UL listed), brown, pre-connected to the fixture, pre-stripped for easy wire connection
- Lifetime warranty on fixture housing
- Available without a lamp

HL100-LED6W
(6 watt MR16 LED lamp included)

HL100-LED5W
(5 watt MR16 LED lamp included)

HL100-LED4W
(4 watt MR16 LED lamp included)



The shroud on the HL100 is easily extendable.

HL200-LED
(LBIPIN-LED-200lm lamp included)



DL50-LED
(4 watt MR11 LED lamp included)



DL100-LED6W
(6 watt MR16 LED Lamp included)

DL100-LED5W
(5 watt MR16 LED Lamp included)

DL100-LED4W
(4 watt MR16 LED Lamp included)



DL200-LED6W
(6 watt MR16 LED Lamp included)

DL200-LED5W
(5 watt MR16 LED Lamp included)

DL200-LED4W
(4 watt MR16 LED Lamp included)




MR16 Down Light LED Lamps Now Come With Enclosed Housing



Down Lights Feature:

- Brass fixture, aged brass finish
- Solid brass knuckle with dial adjustment
- Brass shroud with rubber gasket
- Ceramic bi-pin socket with lamp clip
- 25 Foot wire lead, 16 awg (UL listed), brown, pre-connected to the fixture, pre-stripped for easy wire connection
- Solid brass mounting bracket, aged brass finish (DL100 and DL200)
- Brass mounting nut for precise adjustment (DL100 and DL200)
- Aged brass round mounting base (DL50)
- Mounting screws
- Lifetime warranty on fixture housing
- Available without a lamp



FL50-LED

FL50-LED



BL300-LED10W

BL300-LED10W

BL300-LED10W

BL300-LED8W

BL300-LED8W

BL300-LED8W

BL300-LED8W

BL300-LED10W
BL300-LED10W

BL300-LED8W
BL300-LED8W
BL300-LED8W
BL300-LED8W

BL300-LED8W
BL300-LED8W

BL300-LED10W

BL300-LED10W


Flood Lights Feature:

- Brass fixture, aged brass finish
- Solid brass knuckle with dial adjustment
- Brass face plate with rubber gasket
- Ceramic bi-pin socket
- Clear lens (Optional frosted lens available)
- Double wire lead pre-connected to the fixture, 16 awg (UL listed), brown
 - 25 foot wire lead, pre-stripped for easy wire connection
 - 18 inch wire lead, LED connection ready
- Plastic ground stake (8.5 in; 21.6 cm length)
- Lifetime warranty on fixture housing
- Available without a lamp

In-Ground Lights Feature:

- Brass fixture, aged brass finish
- Clear convex lens
- Solid brass fixture base with two rubber gasket seals
- Solid brass faceplate with four screws
- Ceramic bi-pin socket
- Double wire lead pre-connected to the fixture, 16 awg (UL listed), brown
 - 25 foot wire lead, pre-stripped for easy wire connection
 - 18 inch wire lead, LED connection ready
- Lifetime warranty on fixture housing
- Available without a lamp

FEATURES:



GL100-LED4W

GL100-LED4W

GL100-LED6W
(6 watt MR16 LED lamp included)

GL100-LED5W
(5 watt MR16 LED lamp included)

GL100-LED4W
(4 watt MR16 LED lamp included)

GL150-LED6W
(6 watt MR16 LED lamp included)

GL150-LED5W
(5 watt MR16 LED lamp included)

GL150-LED4W
(4 watt MR16 LED lamp included)

GL160-LED6W
(6 watt MR16 LED lamp included)

GL160-LED5W
(5 watt MR16 LED lamp included)

GL160-LED4W
(4 watt MR16 LED lamp included)

GL170-LED6W
(6 watt MR16 LED lamp included)

GL170-LED5W
(5 watt MR16 LED lamp included)

GL170-LED4W
(4 watt MR16 LED lamp included)

GL180-LED6W
(6 watt MR16 LED lamp included)

GL180-LED5W
(5 watt MR16 LED lamp included)

GL180-LED4W
(4 watt MR16 LED lamp included)

GL190-LED6W
(6 watt MR16 LED lamp included)

GL190-LED5W
(5 watt MR16 LED lamp included)

GL190-LED4W
(4 watt MR16 LED lamp included)

GL200 Features:

- Brass fixture, aged brass finish
- Clear flat lens
- Hex Louver
- Ceramic bi-pin socket mounted to a bracket
- Double wire lead pre-connected to the fixture, 16 awg (UL listed), brown
 - 25 foot wire lead, pre-stripped for easy wire connection
 - 18 inch wire lead, LED connection ready
- Lifetime warranty on fixture housing
- Available without a lamp

- GL200-LED6W**
(6 watt MR16 LED lamp included)
- GL200-LED5W**
(5 watt MR16 LED lamp included)
- GL200-LED4W**
(4 watt MR16 LED lamp included)



WL300-LED5W

WL300 Features:

- Aged brass louvered grate with lamp holder
- Lamp height adjusting track with locking nuts
- ABS housing, black
- Ceramic bi-pin socket
- Double wire lead pre-connected to the fixture, 16 awg (UL listed), brown
 - 25 foot wire lead, pre-stripped for easy wire connection
 - 18 inch wire lead, LED connection ready
- Lifetime warranty on fixture housing
- Available without a lamp

- WL300-LED6W**
(6 watt MR16 LED lamp included)
- WL300-LED5W**
(5 watt MR16 LED lamp included)
- WL300-LED4W**
(4 watt MR16 LED lamp included)



The height of the lamp housing in the WL300 is easily adjustable.



22 WELL LIGHTS



WL100-LED10W
(10 watt PAR36 LED lamp included)

WL100-LED8W
(8 watt PAR36 LED lamp included)

WL100-LED4W
(4 watt PAR36 LED lamp included)

**Available in LED ONLY*



WL200-LED10W
(10 watt PAR36 LED lamp included)

WL200-LED8W
(8 watt PAR36 LED lamp included)

WL200-LED4W
(4 watt PAR36 LED lamp included)

**Available in LED ONLY*

CGWL01-LED10W
(10 watt PAR36 LED lamp included)

CGWL01-LED8W
(8 watt PAR36 LED lamp included)

CGWL01-LED4W
(4 watt PAR36 LED lamp included)

**Available in LED ONLY*



WL100 and WL200 Feature:

- ABS grate, black (WL100)
- Aged brass debris guard with clear glass lens (WL200)
- ABS housing, black
- Lamp retainer ring, stainless steel
- Double wire lead pre-connected to the fixture, 16 awg (UL listed), brown
 - 25 foot wire lead, pre-stripped for easy wire connection
 - 18 inch wire lead, LED connection ready
- Lifetime warranty on fixture housing

CGWL01 Features:

- Heavy brass grate, aged brass finish
- Clear glass convex lens, tempered
- Lamp retainer ring, stainless steel
- ABS housing, black
- Double wire lead pre-connected to the fixture, 16 awg (UL listed), brown
 - 25 foot wire lead, pre-stripped for easy wire connection
 - 18 inch wire lead, LED connection ready
- Lifetime warranty on fixture housing

ALLIANCE 23



Photo Courtesy of: Caity & Drew Photography
Lighting Design by: Visual Concepts, owned by Ken Perez Sr.

24 STEP LIGHTS

TAPE-LED Features:

- 5 Foot LED strip
- Mounting clips included
- 10' wire lead, 16 awg (UL Listed), brown, pre-connected to the fixture, pre-stripped for easy wire connection
- 10 Year warranty on LED components and fixture housing

LED strip

- Beam Angle: 120°
- Beam Spread: Flood
- Color: Warm White
- Color Temperature: 2700K
- Operating Voltage: 10.8Vac - 15Vac
- CRI: Ra>80
- Rated Hours: 30,000
- Ambient Operating Temperature: -40°C ~ +85°C

SL-LED Series Features:

- Brass fixture, aged brass finish
- Mounting bracket, stainless steel, aged brass finish
- Optional frosted lens included
- 10' wire lead, 16 awg (UL Listed), brown, pre-connected to the fixture, pre-stripped for easy wire connection
- 10 Year warranty on LED components and fixture housing

Integrated LED strip

- Beam Angle: 120°
- Beam Spread: Flood
- Color: Warm White
- Color Temperature: 2700K
- Operating Voltage: 10.8Vac - 15Vac
- CRI: Ra>80
- Rated Hours: 30,000
- Ambient Operating Temperature: -40°C ~ +85°C

TAPE-LED-5FT

Integrated LED Step Light

Can be cut down to length

LED strip, 5 Feet


- Watts: 18w
- Light Output: 827 lm (Lumens)

Per 1 Foot:

- Watts: 3.5w
- Light Output: 165 lm (Lumens)



Can be Cut Down to Size



SL65-LED

Integrated LED Step Light

LED strip, 4 chips

- Watts: 1.1w
- Light Output: 110 lm (Lumens)
- Halogen Equivalent: 10w




SL75-LED

Integrated LED Step Light

LED strip, 8 chips

- Watts: 3w
- Light Output: 120 lm (Lumens)
- Halogen Equivalent: 20w




SL85-LED

Integrated LED Step Light

LED strip, 12 chips

- Watts: 4w
- Light Output: 370 lm (Lumens)
- Halogen Equivalent: 30w



SL95-LED

Integrated LED Step Light

LED strip, 20 chips

- Watts: 8w
- Light Output: 660 lm (Lumens)
- Halogen Equivalent: 40w



Mounting bracket is removable for further applications. Optional frosted lens is included with the fixture.

MOST POPULAR

The 7" SL75-LED is our most popular and works in countless applications. The 4" SL65-LED will work great on shorter walls and corners. The 12" SL85-LED is ideal for taller walls and will provide a wider coverage area. The 18" SL95-LED will provide the most powerful and widest output for heavy duty jobs. All of these fixtures come with an optional frosted lens and have the ability to mount without the bracket.

26 STEP LIGHTS

SL100-LED


SL100 Features:

- Brass fixture, aged brass finish
- Solid brass face plate with securing hex screws
- Allen wrench tool to tighten hex screws
- Base plate with adjustable mounting guides
- Ceramic bi-pin socket
- Frosted lens
- 25 Foot wire lead, 16 awg (*UL listed*), brown, pre-connected to the fixture, pre-stripped for easy wire connection
- Mounting hardware screws
- Two extra adjusting hex face plate screws
- Mounting template
- Lifetime warranty on fixture housing
- Available without a lamp

SL50-LED (LBIPIN-LED-200lm lamp included)



SL100-LED (LBIPIN-LED-200lm lamp included)



ALLIANCE 27

SL50 Features:

- Brass fixture, aged brass finish
- Ceramic bi-pin socket
- Frosted lens
- 25 Foot wire lead, 16 awg (*UL listed*), brown, pre-connected to the fixture, pre-stripped for easy wire connection
- Lifetime warranty on fixture housing




Photo Courtesy of: Caity & Drew Photography
Lighting Design by: Visual Concepts, owned by Ken Perez Sr.

SL25-LED
Integrated Surface Mount Step Light



Mounts directly onto desired surface

(Back View)




(Side View)



SL26-LED
Integrated Surface Mount Step Light



SL35-LED
Integrated Surface Mount Step Light



SL36-LED
Integrated Surface Mount Step Light



SL200 and SL300 Feature:

- Brass fixture, aged brass finish
- Solid brass face plate with securing screws
- Ceramic bi-pin socket
- 25 Foot wire lead, 16 awg (UL listed), brown, pre-connected to the fixture, pre-stripped for easy wire connection
- Optional metal set box included
- Lifetime warranty on fixture housing
- Available without a lamp

(Back View)



(Side View)



SL200-LED
(LBIPIN-LED-200lm lamp included)


SL300-LED
(Two LBIPIN-LED-200lm lamps included)

SL25-LED/SL26-LED Features:

- Brass fixture, aged brass finish
- Solid brass louvered face plate with frosted lens (SL25-LED)
- Solid brass open face plate with frosted lens (SL26-LED)
- 25' Wire lead
- 10 Year warranty on LED components and fixture housing
- Integrated LED
 - Watts: 4.5w
 - Color: Warm White
 - Color Temperature: 2700K
 - Operating Voltage: 8Vac-15Vac
 - CRI: Ra>80
 - Halogen Equivalent: 20w
 - Rated Hours: 30,000 Hours
 - Ambient Operating Temperature: -40°C ~ +85°C

SL35-LED/SL36-LED Features:

- Brass fixture, aged brass finish
- Solid brass louvered face plate with frosted lens (SL35-LED)
- Solid brass open face plate with frosted lens (SL36-LED)
- 25' Wire lead
- 10 Year warranty on LED components and fixture housing
- Integrated LED
 - Watts: 9w
 - Color: Warm White
 - Color Temperature: 2700K
 - Operating Voltage: 8Vac-15Vac
 - CRI: Ra>80
 - Halogen Equivalent: 40w
 - Rated Hours: 30,000 Hours
 - Ambient Operating Temperature: -40°C ~ +85°C



30 UNDERWATER LIGHT



UL100-LED5W

UL100 Features:

- Brass fixture, aged brass finish
- Solid brass fixture base
- Solid brass shroud with water tight, sealed clear lens
- Ceramic bi-pin socket
- 25 Foot underwater wire lead, pre-connected to the fixture (also available with 50 Foot and 100 Foot wire leads)
- UL1838 Certified underwater landscape luminaire
- Lifetime warranty on fixture housing
- Available without a lamp



AVAILABLE IN LONGER LEADS

UL100-50FT

(50 Foot wire lead)
Available in LED

UL100-100FT

(100 Foot wire lead)
Available in LED


UL100-LED6W
(6 watt MR16 LED lamp included)

UL100-LED5W
(5 watt MR16 LED lamp included)

UL100-LED4W
(4 watt MR16 LED lamp included)

Wall Sconces Feature:

- Brass fixture, aged brass finish
- Frosted top lens (WS100 and WS200)
- Clear glass top and bottom lenses (WS300)
- Dual Ceramic bi-pin socket
- 25 Foot wire lead, 16 awg (UL listed), brown, pre-connected to the fixture, pre-stripped for easy wire connection
- Lifetime warranty on fixture housing
- Available without a lamp



WS200-LED

AL150

AL150

ALSTEM18-LED

ALSTEM18-LED

WALL SCONCE LIGHTS 31



WS100-LED
(Two LBIPIN-LED-200lm lamps included)



WS200-LED
(Two LBIPIN-LED-200lm lamps included)



WS300-LED6W
(Two 6 watt MR16 LED lamps included)

WS300-LED5W
(Two 5 watt MR16 LED lamps included)

WS300-LED4W
(Two 4 watt MR16 LED lamps included)

32 POST LIGHT



POST100-LED4W

Post Light Features:

- Brass post light, aged brass finish
- Frosted lens panels
- Ceramic bi-pin socket
- Mounting hardware
- 25 foot wire lead, 16 awg(UL Listed), brown, pre-connected to the fixture, pre-stripped for easy wire connection
- Lifetime warranty on fixture housing
- Available without a lamp

POST100-LED6W

(6 watt MR16 LED lamps included)

POST100-LED5W

(5 watt MR16 LED lamps included)

POST100-LED4W

(4 watt MR16 LED lamps included)



DEMO KIT 33

DEMOKIT8

(LED Demonstration Kit)



Quick connects on every wire lead,
for an easy and fast connection

DEMOKIT8 Includes:

- (6) BL200-LED4W
- (2) ALSTEM12-LED
- (2) AL100 Area Light Hats
- (1) TF150 Transformer
- (2) Wire Splitters
- (12) Extra Connectors
- Storage Locker

Demo Kit Features:

- Our industry first double wire leads: fixtures with two 16 awg (UL Listed) brown wire leads pre-connected to the fixture, one 18" and one 25' in length.
- Quick connecting adapters at each wire end making connections fast and easy (not intended for in ground burial)
- A TF150 transformer with an 18" wire lead pre-connected with quick connect adapter
- A compact storage locker making the kit easy to store and transport
- Extra quick connectors
- Door Hangers



it150
150 Watt Intelligent Transformer
Two Commons, Two 14V Taps

it300
300 Watt Intelligent Transformer
Three Commons, Three 14V Taps

Features:
Bluetooth Ready
Phone App Driven
Multiple 14.0v Taps
Astronomical Timer
Lifetime Warranty
FOR LED ONLY


TF300
300 Watt Stainless Steel Transformer Featuring:
- Multiple Taps (12v-15v)
- Built in photocell/timer



TF200
200 Watt Stainless Steel Transformer Featuring:
- One 12 Volt tap only
- Built in photocell/timer



TF150
150 Watt Transformer Featuring:
- One 12 Volt tap only
- Built in photocell/timer



ETF60
60 Watt Electronic Transformer



XF TRANSFORMER ACCESSORIES



(XF150 pictured)

XF150
150 watt Transformer
COM1 COM2 12 13 14 15

XF300
300 watt Transformer
COM1 COM2 12 13 14 15

XF600
600 watt Transformer
COM1 12 13 14 15 16 17 18 COM2

PC
Photocell



3.5 in (7.6 cm)

TIMER
Mechanical Timer
2.5 in (6.4 cm)



Depth: 1.5 in (3.8 cm)

CONNECTION ACCESSORIES

A-LOC
Waterproof Wire Connectors



CS150
Two Brass Connectors and Plastic Lug Caps




CS100
Two Brass Connectors with Set Screws and Plastic Lug Caps in PVC housing




2.5 in (6.4 cm)

9.25 in (23.5 cm)

RMB
Aged Brass Round Mounting Base



GUTTERMOUNT
Aged Brass Gutter Mount



RISERADJ-BRASS
Adjustable Brass Riser



RISER18
18" Aged Brass Riser



RISER12
12" Aged Brass Riser



RISER6
6" Aged Brass Riser




STAKE-P3
Three Prong Ground Stake



C-CLAMP



PERMAPOST
Heavy Duty Ground Stake



PRODUCT WARRANTY:

Alliance Outdoor Lighting warrants its products against defects in material and workmanship. Without charge, Alliance Outdoor Lighting will either repair or replace (Alliance Outdoor Lighting reserves the right to decide between repair or replacement) any properly installed Alliance Outdoor Lighting product that fails under normal operating conditions within the specified warranty period.

- **Brass and Copper fixtures:** All have a lifetime warranty for all castings and housings.
- **XF Series Transformers:** All XF series transformers carry a lifetime warranty on enclosures. All transformer windings carry a lifetime warranty.
- **TF Series Transformers:** Two year warranty.
- **Integrated LED fixtures:** All Alliance LED integrated fixtures carry a 10 year warranty
- **LED Lamps:** Five year warranty.
- **Halogen Lamps:** Do not carry a warranty
- **Timers and Photocells:** Do not carry a warranty
- **ETF60 Transformers:** Do not carry a warranty

All products are warranted from the date of invoice, provided it is returned to the Alliance Outdoor Lighting distributor from where it is purchased. Our factory inspection determines it to be defective under the terms of the warranty. This warranty covers only equipment manufactured by Alliance Outdoor Lighting and does not extend to transportation, installation, labor compensation, or replacement charges, nor does it apply to any equipment of another manufacturer used in conjunction with Alliance Outdoor Lighting equipment.


NOTE: All Alliance Outdoor Lighting products are designed to be repaired in the field by a qualified lighting installer. All service parts are readily available and we encourage field repairs as a significant cost and labor savings which can be realized by the installer. All warranted components, as stated in the above warranty, which are installed in the field, will be honored.

1ST INDUSTRY DOUBLE WIRE LEAD



We Provide the Wire
You Save on Labor

Connect the **Long 25'** Lead to the **Short 18"** Lead



For LED installations only

Fixtures					
Part #	Qty	Part #	Qty	Part #	Qty
AREA LIGHT HATS		DOWN LIGHTS		PATH LIGHTS	
AL100		DL50		PL100	
AL150		DL100		PL200	
AL200		DL200		PL250	
AL300		HL100		WALL SCONCES	
AL400		HL200		WS100	
AL500		IN-GROUND LIGHTS		WS200	
AL550		GL100		WS300	
AL600		GL150		UNDERWATER LIGHT	
AL700		GL160		UL100	
AL750		GL170		UL100-50FT	
AL800		GL180		UL100-100FT	
AL850		GL190		POST LIGHT	
TIKI		GL200		POST100	
AREA LIGHT STEMS		STEP LIGHTS		Accessories	
ALSTEM12		WL100-LED		C-CLAMP	
ALSTEM18		WL200-LED		GUTTERMOUNT	
ALSTEM24		WL300		RISER6	
ALSTEM60		CGWL01-LED		RISER12	
ALSTEMADJ		BULLET LIGHTS		RISER18	
BL50		SL25-LED		RISERADJ-BR	
BL100		SL26-LED		RMB	
BL200		SL35-LED		STAKE-P3	
BL300-LED		SL36-LED		PERMAPOST	
BL350		SL65-LED		GL160-TOP	
CGBL01		SL75-LED		GL170-TOP	
FLOOD LIGHTS		SL85-LED		GL180-TOP	
FL50		SL95-LED		GL190-TOP	
FL100		SL50			
FL200		SL100			
		SL200			
		SL300			

LED Lamps	
Part #	Qty
MR11	
LMR11-LED-4W-F	
MR16	
LMR16-LED-4W-F	
LMR16-LED-4W-F-2700K	
LMR16-LED-4W-NS	
LMR16-LED-4W-WF	
LMR16-LED-4W-250lm	
LMR16-LED-5W-F	
LMR16-LED-5W-F-2700K	
LMR16-LED-5W-NS	
LMR16-LED-5W-WF	
LMR16-LED-310lm	
LMR16-LED-6W-F	
LMR16-LED-6W-F-2700K	
PAR36	
LPAR36-LED4W-F	
LPAR36-LED4W-WF	
LPAR36-LED8W-F	
LPAR36-LED8W-WF	
LPAR36-LED10W-F	
LPAR36-LED10W-WF	
BIPIN/G4	
LBIPIN-LED-200lm	
LBIPIN-LED-250lm	

Transformers	
Part #	Qty
IT SERIES	
IT150	
IT300	
XF SERIES	
XF150	
XF300	
XF600	
TF SERIES	
TF150	
TF200	
TF300	

Accessories	
Part #	Qty
A-LOC	
CS100	
CS150	
ETF60	
PC	
TIMER	



800.930.6225
info@allianceoutdoorlighting.com
www.allianceoutdoorlighting.com



ALLIANCE

2017 PRODUCT CATALOG
800.930.6225
www.allianceoutdoorlighting.com
www.doyouknowalliance.com